



Tile Floor Sealant Addendum

Dynasty®
Executive®
Signature®
Navigator®

The information printed here reflects product design, fabrication, and component parts at the date of printing. Due to product improvements, changes during the model year and/or transcription errors that may occur, information represented within this document may not be accurate at the time of purchase. Please confirm any information with the dealership.

The manufacturer reserves the right, at any time, to make changes in product design or material or component specifications as its sole option, without notice. This includes the substitution of components of a different brand or trade name, which will result in comparable performance. All information printed in this document is subject to change after the date of printing. Some features shown or mentioned in this document are optional and may only be available in selected floorplans.

©Copyright Monaco Coach Corporation. All rights reserved. All trademarks or registered trademarks are property of their respective holders. Brand name products of other companies mentioned in this addendum are not endorsed by Monaco Coach Corporation.

TILE FLOOR SEALANT

It is recommended that a sealant should be applied to the tile floor and grout to maintain the quality of finish and prevent discoloring of the grout from soils and spills. One pint of 511 Sealant is provided, and will be a sufficient quantity to seal the floor. The floor surface will need to be clean and dry before the sealant is applied.

After application, the floor will be ready for careful use after five hours. The sealant requires 72 hours to cure completely.



NOTE: It is recommended to first test using a small amount of sealant on an inconspicuous area. Avoid getting sealant onto surfaces other than the flooring.

To Apply:

1. Extend slide room(s) and clean floor.
Allow floor and grout to thoroughly dry.
2. Working from rear towards doorway, apply sealant direct from container onto a cloth towel or broom handle applicator.
3. Apply only enough sealant to wet surface.
Do not allow sealant to puddle in grout lines. Extra care should be used to make sure all grout has been sealed. Only one application is necessary.
4. Allow five hours to dry. Sealant will fully cure in 72 hours.



070182



NOTE: If a spill occurs before sealant has cured, it may be necessary to clean and retreat area with sealant as needed.



CAUTION: Product contains petroleum distillates. Open windows, vents and doors to provide adequate airflow during application. See the “Caution” statement on the back of the container for further information.



Monaco Coach Corporation (NYSE:MNC) • 91320 Coburg Industrial Way, Coburg, Oregon 97408
Warranty/Technical Support • 877-466-6226
www.monacocoach.com

MNC
LISTED
NYSE

