

***Wheel Mounting
Addendum***

2004

Presidential Travel Trailer

The information printed here reflects product design, fabrication, and component parts at the date of printing. The manufacturer reserves the right, at any time, to make changes in product design or material or component specifications as its sole option, without notice. This includes the substitution of components of a different brand or trade name, which will result in comparable performance. All information printed in this document is subject to change after the date of printing. Due to product improvements, changes during the model year and/or transcription errors that may occur, information represented within the owner's manual and/or this document may not be accurate at the time of your purchase. Please confirm any information with your dealer.

The following information supersedes the information published in the 2004 Presidential Travel Trailer Owner's Manual on pages 64 and 65 section 2. Please utilize the information provided henceforth.

©Monaco Coach Corporation. All rights reserved. All other trademarks or registered trademarks are property of their respective holders. Brand name products of other companies mentioned in this addendum are not endorsed by Monaco Coach Corporation.

The following information supersedes the information published in the 2004 Presidential Travel Trailer Owner's Manual on pages 65 and 66 section 2. Please utilize the information provided.

WHEEL MOUNTING

The travel trailer comes with heavy-duty wheels. When buying additional wheels get the same type as those installed on the fifth wheel. Check the wheel lug bolts before every trip.

1. After demounting old wheel, remove all dirt, rust, grease and oil from stud threads. Do not lubricate threads.
2. Position wheel on travel trailer. **Inspect** to insure full contact between the mounting surface (seat pads) of wheel and mounting surface of hub and brake drum.
3. Start wheel nuts on stud.
4. Finger tighten top nut. Rotate wheel so that the number two nut is at top. Finger tighten remaining nuts in numerical (crisscross) order; always tighten nuts in top position.
5. Repeat Step 4, rotating wheel and finger tightening nuts until all nuts are snug.
6. Tighten nuts as described under "wheel torque requirement."
7. After wheels (with tires) have been mounted, visually inspect them to ensure non-interference with body or other component parts. Be sure to inspect wheels in all possible positions (extreme turn, etc.).
8. Only specially trained persons using proper equipment should mount or demount pneumatic tires. Serious or fatal injuries can result from using improper mounting procedures.



NOTE: Check the fit of the lug wrench. An oversized wrench results in mutilated lug nuts.



WARNING: Maintain proper torque on lug nuts or wheel bolts. Failure to do so may result in serious injury or property damage.

Wheel Torque Requirements:

It is extremely important to apply and maintain proper wheel mounting torque on the travel trailer axle. Torque is a measure of the amount of tightening applied to a fastener (nut or bolt) and is expressed as length times force. For example, a force of 90 pounds applied at the end of a wrench one foot long will yield 90 lbs ft of torque. Torque wrenches are the best method to assure the proper amount of torque is being applied to a fastener.



NOTE: Wheel nuts or bolts must be applied and maintained at the proper torque levels to prevent loose wheels, broken studs and possible dangerous separation of wheels from the axle.

STEEL WHEELS

Be sure to use only the fastener matched to the cone angle of the wheel (usually 60° or 90°). The proper procedure for attaching the wheels is as follows:




WARNING: Do not exceed the maximum amount of torque. Over-torquing can result in damage to the lug nuts.


- Start all bolts or nuts by hand to prevent cross threading.
- Tightening of the fastener should be done in stages.
- Following the recommended sequence, tighten fastener per wheel torque chart.
- Wheel nuts/bolts should be torqued before first road use and after each wheel removal. Check and torque after the first 10 miles, 25 miles and again at 50 miles. Check periodically thereafter.

TORQUE SEQUENCE - STEEL WHEELS

Wheel Size	First Stage	Second Stage	Final Stage
15"	20-25 foot lbs.	50-60 foot lbs.	90-120 foot lbs.
16"	20-25 foot lbs.	50-60 foot lbs.	90-120 foot lbs.



090291c



130154



NOTE: If the tire and wheel is removed for any reason, the wheel installation procedure listed above must be followed.

ALUMINUM WHEELS

Be sure to use only the fastener matched to the cone angle of the wheel (usually 60° or 90°). The proper procedure for attaching the wheels is as follows:




WARNING: Do not exceed the maximum amount of torque. Over-torquing can result in damage to the lug nuts.


- Start all bolts or nuts by hand to prevent cross threading.
- Tightening of the fastener should be done in stages.
- Following the recommended sequence, tighten fastener per wheel torque chart.
- Wheel nuts/bolts should be torqued before first road use and after each wheel removal. Check and torque after the first 10 miles, 25 miles and again at 50 miles. Check periodically thereafter.

TORQUE SEQUENCE - ALUMINUM WHEELS

Wheel Size	First Stage	Final Stage
15"	80-90 foot lbs.	120-130 foot lbs.
16"	80-90 foot lbs.	120-130 foot lbs.



090291c



130154



NOTE: If the tire and wheel is removed for any reason, the wheel installation procedure listed above must be followed.



Monaco Coach Corporation
91320 Coburg Industrial Way
Coburg, OR 97408
800-634-0855
www.monaco-online.com

Indiana Operations
1809 W Hively
Elkhart, IN 46517
800-650-7337
www.holidayrambler.com

Warranty/Technical Support
Toll Free 877-466-6226