

# Auto Fill Addendum

---

## 2007 Navigator

The information printed here reflects product design, fabrication, and component parts at the date of printing. The manufacturer reserves the right, at any time, to make changes in product design or material or component specifications as its sole option, without notice. This includes the substitution of components of a different brand or trade name, which will result in comparable performance. All information printed in this document is subject to change after the date of printing. Due to product improvements, changes during the model year and/or transcription errors that may occur, information represented within the owner's manual and/or this document may not be accurate at the time of your purchase. Please confirm any information with your dealer.


The following information supercedes previous information and applies to all motorhomes equipped with a Roadmaster Chassis.

©Monaco Coach Corporation. All rights reserved. All other trademarks or registered trademarks are property of their respective holders. Brand name products of other companies mentioned in this addendum are not endorsed by Monaco Coach Corporation.

The following information supersedes the information in the 2007 Navigator Owner's Manual on page 143 under the "City Hookup" and "Fresh Tank Fill" subheadings.

### **Auto Fill**

The motorhome is equipped with an "AutoFill/City Water" switch located in the water service bay. The switch must be in the "AutoFill" position to fill the fresh water tank. A valve behind the water service bay will automatically close when the fresh water tank is 98% full. Place the switch in the "City Water" position to bypass the fresh water tank and pressurize the system with a city water source.



- ◆ Remove hose plug and install a water pressure regulator to the water hose.
- ◆ Pull hose from reel and connect the water hose to a City Water hook-up.
- ◆ Place the AutoFill/City Water switch in the "Up" position to engage the fresh tank auto-fill feature. A valve behind the plumbing manifold will automatically close when the fresh tank is 98% full.
- ◆ Turn the motorhome water pump on (switches located in service center, galley and bathroom) to access water from the fresh water tank. When the water level in the fresh water tank is depleted to 80%, the valve will automatically open and refill the tank to 98%.

#### **NOTE:**


**Cycle the AutoFill/City Water switch to fill the fresh water tank at any time.**

#### **NOTE:**

**If the tank fails to fill while in Automatic Fill mode (perhaps because an external water valve is inadvertently shut), the fill solenoid valve will deactivate after one minute to prevent heat damage.**

### **City Hook-Up**

- ◆ Remove hose plug and install a water pressure regulator to the water hose.
- ◆ Pull hose from reel and connect the water hose to a City Water hook-up.
- ◆ Place the AutoFill/City Water switch in the "Down" position.
- ◆ Turn on the water supply.
- ◆ The water pump can be on or off. It will not affect the water pump to leave it on.



#### **CAUTION:**

**Some outside water sources develop high water pressure, particularly in mountainous regions. High water pressure is anything greater than 55 psi (pounds per square inch). Excessive water pressure may cause leaks in water lines and/or damage the water heater. An additional pressure regulator can be connected to the city water faucet to regulate the pressure to the potable water hose. Excess pressure on a hot day can cause the water hose to swell and burst.**



# HOLIDAY RAMBLER®

Monaco Coach Corporation  
91320 Coburg Industrial Way  
Coburg, OR 97408  
800-634-0855  
[www.HolidayRambler.com](http://www.HolidayRambler.com)

---

Warranty/Technical Support  
Toll Free 877-466-6226